

# KL-BR40-XXYYZZCCTTP



### Advantages:

- Long Life
- Energy Efficiency
- Ecologically Friendly
- Durable Quality
- Design Flexibility
- Operational in Extremely Cold or Hot Temperatures
- Instant Lighting, Low Voltage & Frequent Switching

### Technical Characteristics

Color Temp:	27K, 30K, 40K, 50K	LED Quantity	280 pcs.
CRI	>80	Housing	PC+AL
Lumen	1090LM		
Input Power	14W		
Viewing Angle	120°		
Input Voltage	90-135Vac		
PFC	>90		
Light efficacy	78 lumen/watt		
Waterproof Rating	IP64		
Equivalent	75W		

### Application:

- Widely used in wall sconces, chandeliers, ornamental fixtures, bath bar, floor and table lamps, display counters and under cabinets.
- Used at retail stores, art galleries and in recessed and track light.

### Technical Specifications

#### Listings

##### UL Listing:

UL code: E472587



IP64: Suitable for wet locations

#### Others

##### Warranty time: 5 years

To prevent injury or damage to property, this product must be installed in accordance to National Electrical Code (NFPA70) in the US or Canadian Electrical Code (CSA 22.1) in Canada.

Risk of fire or electric shock. The electrical rating of these products are 100-277 Vac, the installer must determine whether they have 100-277 V at the luminaire before installation.

Risk of fire or electric shock. Installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation. Contact a qualified electrician.

To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.

Disconnect power before installing the product or servicing it.

Wait until fixture has cooled down before installing or servicing the fixture.

Min. 90°C Supply Conductors

Warranty Period assumes that the Products are operated for less than 8 hours per day.

#### Operating conditions

Max Operating temperatures:  
105°F

#### Application:

Outdoor/Indoor

#### Life Span:

25K hours



# KL-BR40-XXYYZZCCTTP

## Order Information

KL - BR40 - WATT - XXYYZZCCTTP - CCT

KL — BR40 — 14 — XXYYZZCCTTP —  
30K: 4000K  
40K: 4500K  
50K: 5000K

KL - BR40 - 14 - XXYYZZCCTTP -