

KL240SRKXX-HV



Advantages

- UL DLC certificate
- CREE Chip, SUNON fan
- High CRI
- Mean Well IP65 driver,
- UL Input voltage 100-277VAC
- No UV or IR in the beam
- Easy to install and operate
- Energy saving, long service life
- Light is soft and uniform, safe to eyes
- Instant start, NO flickering, NO humming
- Green and eco-friendly without mercury.

Technical Characteristics

Color Temp:	4K, 4K5, 5K	LED quantity	112 PCS
Lumen	22000-28000LM		
Input Power	240W		
Viewing Angle	120°		
Input Voltage	200-480VAC	50/60Hz	
CRI	>70		
PFC	>0.9		
Waterproof Rating	IP40		
Equivalent	1800W incandescent / 500W CFL		

Application:

Outdoor Pole/ Arm-mounted Area and Roadway Luminaires
 High-bay Luminaires for Commercial and Industrial Buildings

Technical Specifications

Listings

UL listed

DLC Listed

IP40 Waterproof rating



Others

Warranty time: 5 years

To prevent injury or damage to property, this product must be installed in accordance to National Electrical Code (NFPA70) in the US or Canadian Electrical Code (CSA 22.1) in Canada.

Risk of fire or electric shock. The electrical rating of these products are 100-277 Vac, the installer must determine whether they have 100-277 V at the luminaire before installation.

Risk of fire or electric shock. Installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation. Contact a qualified electrician.

To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.

Disconnect power before installing the product or servicing it.

Wait until fixture has cooled down before installing or servicing the fixture.

Min. 90°C Supply Conductors

Warranty Period assumes that the Products are operated for less than 8 hours per day.

Operating conditions

Operating temperatures:

-20°C TO 45°C

Operating Humidity:

20%-90% RH

Storage Temperature

-30°C TO 80°C

Storage Humidity:

10%- 90% RH

Application:

Outdoor

Dimensions



