


# 4FT LED Prismatic lens Wraparound

## Product photos & Advantages



## Technical Characteristics

### KLPWA-4FT40W-XX

#### Driver Info

Type:	Constant Current
120V:	Yes
277V:	Yes
480V:	N/A
Watts:	40W

#### LED Info

Color Temp:	4000K, 5000K
Color Accuracy:	80CRI
L70 Lifespan:	50000
Lumens:	4200LM
Efficacy:	105LM/W

Suitable for damp location and operation in ambient not exceeding 40 °C(104 F )  
Meets the general and decoration lighting environment such as:Office light, Restaurants,Hotels,Subway Stations,School and Hospital.Hallway and lobbies, Meeting rooms.

Color: White  
Weight: 1.66kg (3.67 lbs)



## Technical Specifications

### Listings

#### ETL Listing:

Suitable for damp location.  
ETL code: 4007551

#### IESNA LM-79 & IESNA LM-80 Testing:

This product has been tested by an independent laboratory in accordance with IESNA LM-79 and 80, and have received the Department of Energy" Lighting Facts" label.

### LED Characteristics

#### Lifespan:

50,000-hour LED lifespan based on IES LM-80 results and TM-21 calculations.

#### LEDs:

Long-life,high-efficiency SMD2835, patent free.

#### Color Uniformity

CCT(Correlated Color Temperature) follows the guidelines of the American National Standard for Specifications for the Chromaticity of Solid State Lighting( SSL) Products, ANSI C78.377-2015.

### IP Rating:

Damp location

### Finish:

Our environmentally friendly polyester powder coatings are formulated for high-durability and long-lasting color, and contain no VOC or toxic heavy metals.

### Green Technology:

Mercury and UV free RoHS compliant components  
Polyester powder coat finish formulated without the use of VOC or toxic heavy metals.

### Electrical

#### Driver:

Constant Current, Class 2, 100-277Vac,50/60HZ,

#### THD:

<20%

#### Power Factor:

>0.9

### Construction

#### Temperature:

-4°F~+104°F (-20°C~40°C)

#### Housing:

Die formed painted steel

#### Lens:

Prismatic PC Cover

#### Mounting:

Surface mount

### Warranty

#### 5 Yr Limited Warranty:

Fixture operation and paint finish are covered for a period of 5 years.


### Order Information

KL	PWA	SIZE	WATT	CCT			
		4FT	40W	40K: 4000K 50K: 5000K			


KL	PWA	4FT	40W	4000K / 5000K			
----	-----	-----	-----	---------------	--	--	--

# 4FT LED Prismatic lens Wraparound


## Lux Chart/Photometrics



Height	Average Lux (lx)	Light range (dia.)
1M	595.6	215.07cm
2M	148.9	430.13cm
3M	66.2	645.2cm
4M	37.2	860.26cm
6M	23.8	1075.33cm



## Spring Design



## Packaging

8pcs/CTN G.W.:19.5KG Dimension: 51.8"L\*12"W\*11.8"H(1316mm\*306mm\*300mm)

