

KL-A19-9.5YYZZCCTTP



Advantages:

- Long Life
- Energy Efficiency
- Ecologically Friendly
- Durable Quality
- Design Flexibility
- Operational in Extremely Cold or Hot Temperatures
- Instant Lighting, Low Voltage & Frequent Switching

Technical Characteristics

Color Temp:	2700K, 3000K, 4000K, 5000K
CRI	>80
Lumen	800 LM
Input Power	9.5W
Viewing Angle	360°
Input Voltage	90-135Vac
PFC	>90
Light efficacy	108-115 LM/W
Waterproof Rating	IP64
Equivalent	60W

Application:

- Widely used in wall sconces, chandeliers, ornamental fixtures, bath bar, floor and table lamps, display counters and under cabinets.
- Used at retail stores, art galleries and in recessed and track light.

Technical Specifications

Listings

UL Listing:

UL code: E472587

ENERGY STAR

IP64: Suitable for wet locations



Others

Warranty time: 5 years

To prevent injury or damage to property, this product must be installed in accordance to National Electrical Code (NFPA70) in the US or Canadian Electrical Code (CSA 22.1) in Canada.

Risk of fire or electric shock. The electrical rating of these products are 100-277 Vac, the installer must determine whether they have 100-277 V at the luminaire before installation.

Risk of fire or electric shock. Installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation. Contact a qualified electrician.

To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.

Disconnect power before installing the product or servicing it.

Wait until fixture has cooled down before installing or servicing the fixture.

Min. 90°C Supply Conductors

Warranty Period assumes that the Products are operated for less than 8 hours per day.

Operating conditions

Max Operating temperatures:


105F

Application:

Outdoor/Indoor

KL-A19-9.5YYZZCCTTP

Order Information



Package

	Size	Qty/ Carton
Outer box	213x65x118 MM	4 PCS

