

KLJF40T8XX8F



Advantages:

- 50,000 hours lifespan
- 5 years warranty
- No UV emission
- Suitable for damp or dry environments
- Mercury and lead free
- End to end mounting and wiring
- 80% more energy saving compared with traditional lamps
- 4ft linear fixture can be linkable up to 8ft linear fixture
- Easy and secure installation
- Uniformity lighting distribution

Technical Characteristics

Color Temp:	4K, 4K5, 5K, 5K7	Size	2371x31.5x34.5mm
CRI	>80	Lens	Clear/Frosted
Lumen	4400 - 4800 lm		
Input Power	40W		
Beam Angle	120°		
Input Voltage	100-277VAC/50-60Hz		
PFC	>0.9		
Life time	50000 hours		
Power Input	One end Input		

Application:

- Supermarket lighting
- Workshop facility lighting
- Education facility lighting
- Airport and station lighting
- Other commercial applications

Housing Color: White

Technical Specifications

Listings

UL Listing:

UL code: E473338

DLC Listed



UL Number : E473338

Others

Warranty time: 5 years

To prevent injury or damage to property, this product must be installed in accordance to National Electrical Code (NFPA70) in the US or Canadian Electrical Code (CSA 22.1) in Canada.

Risk of fire or electric shock. The electrical rating of these products are 100-277 Vac, the installer must determine whether they have 100-277 V at the luminaire before installation.

Risk of fire or electric shock. Installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation. Contact a qualified electrician.

To prevent wiring damage or abrasion, do not expose wiring to edges of sheet metal or other sharp objects.

Disconnect power before installing the product or servicing it.

Wait until fixture has cooled down before installing or servicing the fixture.

Min. 90°C Supply Conductors

Warranty Period assumes that the Products are operated for less than 8 hours per day.

Operating conditions

Operating temperatures:

-10°C TO 30°C

Operating Humidity:

20%-90% RH

Storage Temperature

-20°C TO 50°C

Storage Humidity:

10%- 75% RH

Application:

Indoor



KLJF40T8XX8F

Order Information

KL - JF - Watt - T8 - Color Temp - Size

KL - JF - 40 - T8 -
4K
4K5
5K
5K7

KL - JF - 40 - T8 - - 8F